



Padding shall be molded to meet or exceed all standards set forth by the NCAA, National High School Federation and FIBA. Padding shall be cellular construction with a skin of an average minimum thickness of 3/50". The skin shall be produced integral to the cushion using a self-skinning molding process. The tear strength of the skin shall be a minimum 125 psi. The padding system shall be capable of mounting to all brands and styles of 72" rectangular backboards by means of eight bolts (provided). A steel track molded into the padding shall provide rigidity and strength to the mounting system. The corners of the padding shall be molded square for maximum safety and shall not require mitering, gluing or forming for attachment. All hardware shall be provided. The two section padding system shall be available in official Gray, Royal, Navy, Columbia Blue, Scarlet, Orange, Gold, Kelly Green, Forest Green, Black, Maroon, Purple, Vegas Gold, Cardinal, Brown, Burnt Orange and Pink. Colors shall be continuous throughout the thickness of the padding, not only on the skin. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. The warranty shall extend for 10-years and cover tearing and deterioration, as well as detachment from the backboards and weigh approximately 12#.



PRODUCT SPECIFICATION

BA68U DuraSkin RECTANGULAR BACKBOARD PADDING

REVISED 8/1/17